

::: PARAFFIN SOLUTION 5%

Description:

Is a 5% liquid paraffin wax of particularly high quality, dissolved in styrene. Can be mixed with all polyester resins and vinylester resins. Available in 1 litre and 10 kg

Application:

To be mixed under all polyester resins, gel coats and top coats to obtain an adhesive-free surface.

Data on delivery:

| | |
|---------------|---------------------------------|
| Color: | colourless |
| Viscosity: | 700 mPas |
| Mass density: | approx. 0.90 gr/cm ³ |
| Shelf life: | 6 months in closed packaging |
| Consistency: | liquid |

Technical data:

| | |
|--------------|----------------|
| Consumption: | 0,5 - 2,5% |
| Shore: | not applicable |

Processing:

Add in a 0.5 to maximum 2.5 % ratio to the resin while stirring continuously. Too much paraffin can affect the adhesion of the following layers and can lead to a matt sheen of the surface. After mixing the paraffin, add the hardener.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.

The information on this page concerns technical instructions and has been compiled to the best of our knowledge. However, it shall not constitute grounds for any liability on our part.