

:: PREMIUM RELEASE AGENT LIQUID

Description:

Is a liquid release agent for processing at a high rate. Formulated to dry quickly. Very easy to apply and remove afterwards. Temperature resistant up to 140°C. Available in 500 ml and 10 lt packs.

Application:

As a basic release agent for de-moulding in a polyester form both for new and used moulds.

Suitable for polyester and epoxy.

Can be applied in aluminium and steel moulds. The surface to be de-moulded must be dry before applying the release wax.

Data on delivery:

Color	off-white
Viscosity	180 mPas
Mass density	approx. 0,72 gr/cm ³
Shelf life	18 months in closed container
Consistency	liquid

Technical data:

Consumption	10 gr/m ²
Shore	not applicable

Processing:

Always ensure a smooth and clean form. Apply with a soft cloth. Apply 4 to 6 thin layers. Wait 5 minutes between coats until the solvents have evaporated from the release agent. In case of a first de-molding, use the wax for at least 6 to 8 layers.

Note: Shake well before use!

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: water and for hands: handcleaner.

The information on this page concerns technical instructions and has been compiled to the best of our knowledge. However, it shall not constitute grounds for any liability on our part.