

: : POOL RENOVATION KIT

Description:

Is a kit with all needed products for DIY-renovation of an existing swimming pool made of polyester, which needs to be recoated or repainted due to osmosis.

Available in 5 colours: light gray (ral 7035), gray (ral 7004), white, beige and pastel blue.

As per extra, we propose a kit with accessories. This contains all tools and accessories for processing the products.

Application:

As a renovation system for the DIY-repair of a glass fiber reinforced polyester swimming pool. This system can be applied to old polyester layers. In addition to reinforcing and repairing the damaged surface, the coating makes the whole waterproof and osmosis-resistant again in the right color.

Data upon delivery :

Reinforcement material:	Vinylester laminating resin	80kg
	Glass mat PB 300 gr/m ² 15 Tex fine mat	80sqm
Top coat:	Polyester precoat type T40BT	20 kg
	Polyester topcoat type LT40SB	20 kg
Harder:	Hardener MEKP for vinyl ester, T40BT and LT40SB	2.5 kg

PVC primer for the PVC connections is not standard with this kit. This can be ordered under number: UPH01100063 or UPH01100059

The tools are not standard with the kit. These can be ordered separately or in a complete set. This set can be found under number KIT50030200 and contains the following products:

* Bleed roll Alu 12 x 140	1 pc
*Rolls for G4, H35 ISO resin, T40BT and LT40SB:	10 x 10 cm
	10 x 18 cm
* Long handle for roll 10 cm	2 pcs
* Handle for roll 18 cm	2 st
* Paint tray(s)	10 st
* Plastic bucket 3.3 L	10 st
* Stir sticks 40 cm wood	10 st
* Graduated cylinder 100 ml	1 st
* Sandpaper P80 sheet	10 st
* Cleaning agent M	1 l
* Glove Super nitrile (size 10)	2 pcs
* Overall PP Shield with hood xl	1 pc

Processing:

Step 1: Prepare the surface well; dry, grease-free, as smooth as possible.

Step 2: Coat the surface with vinylester laminating resin and glass fiber. Don't forget to deair with the bleed alu roll!

Step 3: Apply the precoat T40BT.

Step 4: Apply the top coat LT40SB.

TIP: Wait one week (= 7 days) before filling the pool with water!!

Please refer to our extensive processing information on swimming pool renovation for more details. You will find this information on our website. Also watch our instruction video about the construction of a swimming pool.

Safety:

Vinylester resin contains styrene and must therefore be treated in accordance with the safety regulations.

Always wear appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone.)

The information on this page is technical guidance and has been compiled to the best of our knowledge. However, it never gives rise to any liability on our part.