

**:: POLISH S4 PROTECT WAX**

*Description:*

SL polish S4 protect Wax is a wax-based liquid sealing emulsion. S4 protect wax contains very fine high-quality ingredients with cleaning properties that do not leave scuff marks.

*Application:*

Universal wax for protecting plastic and FRP from ageing. Neutral product and easy to use. Easy to apply and polish out. Protection against oxidation. Due to the UV filters, the colour of the paint or gelcoat will retain its colour significantly longer.

*Data on delivery:*

Colour	white
Viscosity	liquid dispersion
Specific gravity	approx. 0.93 g/cm <sup>3</sup>
Shelf life	3 years from production date

*Technical data:*

Consumption	5-10 gr/m <sup>2</sup>
Shore	irrelevant

*Processing:*

Always ensure a dry and grease-free surface. Shake well before use. Apply the dispersion with a soft microfibre cloth and rub it out as thinly as possible in circular motions. Max. area 70 cm x 70 cm. Further polish with a soft cloth without putting pressure on the surface. This can also be done with a polisher with a soft cloth.

Processing temp: 15-25 °C

In extreme weather conditions, it is recommended to apply 2 coats of wax at 2-hour intervals.

*Security:*

Cleaning agent for tools: water and soap.

---

The information on this page concerns technical instructions and has been compiled to the best of our knowledge.