: : EGALINE

Description:
A calcium sulfate-based self-leveling compound for leveling floors. Used for smoothing and leveling uneven floor surfaces. Suitable for areas with low moisture exposure, both on heated and unheated substrates. Available in 25 kg packaging.

Application:
Self-leveling compound according to DIN standard EN 13813, suitable for layer thicknesses from 2 mm to 30 mm. Fast curing and suitable for indoor applications. Can be applied on cement screeds, calcium sulfate screeds, concrete, dry construction screeds, hollow floors, tile support elements, and well-adhering tiled floors.

Delivery Characteristics:

Colour	Grey
Viscosity	Not applicable
Specific gravity	N.A
Shelf life	12 months in unopened packaging
Consistency	Powder

Technical Data:

Consumption	1.7 kg per m² per mm
Flexural strength	7 N/mm²
Compressive strength	20 N/mm²

Processing:
Use a clean mixing bucket and fill it with the powder. Add the powder to water in a ratio of 4:1 to 5:1. Mix for 3-5 minutes. Working time: 30 minutes. Mix thoroughly and pour the mixture onto the dry and, if necessary, pre-treated substrate. Spread with a notched trowel until the desired layer thickness has been achieved. Apply in a single layer and try to avoid high temperatures, direct sunlight, and drafts. Pay attention to the maximum moisture content present in the substrate.

Safety:
Cleaning agent for tools: water.
Not classified as hazardous goods.

The information on this page concerns technical instructions and has been compiled to the best of our knowledge. However, it can never give rise to any liability on our part.