

: STRIPPER

Description:

This paint remover has been specially developed for removing old layers of paint based on 1 and 2 component polyurethane lacquers, epoxy and paints. Also suitable for removing old antifouling layers, without affecting the polyester. Contains no CFCs or methylene. Product is virtually odourless, environmentally friendly and biodegradable.

Available in 0.5 kg, 1 kg and 5 kg packaging.

Application:

It takes away all old layers of paint so that they can be easily and quickly removed with a spatula, sandpaper or steel wool. Particularly for cold-hardening plastics, wood, glass, metal, stone, etc. Specially developed for removing DD-Lak, Topcolor, antifouling and old layers of paint, such as Urki-Voc and Urki-Nato. Also Epoxy BN can be removed with it.

Data on delivery:

Colour	beige
Viscosity	40000 mPa's
Specific weight	approx. 1-1.2 g/cm ³
Shelf life	12 months
Consistency	paste/thixotropic

Technical data:

PAINT TYPE	consumption in g/m ²	Effect after: time in minutes
2K varnish (200 µm)	100-200	10-20
2K varnish (400 µm)	150-300	20-60
Emulsion paint (3 layers)	250-500	120-300
Emulsion paint (10 layers)	400-800	720-960
Emulsion paint (25 layers)	700-900	1440-2880
Dispersion plaster (3 mm)	500-900	720-1440
Carpet Glue (1 Layer)	250-400	60-240
Acrylic Paint (2 Layers)	200-400	60-240
PU Coatings (3 mm)	500-900	480-960
Glaze on Wood (4 Layers)	250-400	10-40
2K Tar Oil Coating (0.5 mm)	400-700	1080-1440
Wax Stains (3 Layers)	100-300	60-180
1K EP Coating (250 µm)	400-800	240-2880
2K EP Coating (350 µm)	500-950	1440-5520
Wallpaper (3-5 Layers)	500-900	120-240

Processing:

Always ensure a dry surface. Apply the paste with a spatula or flat brush. Allow this to soak in (see table above) depending on the number of layers and the quality of the paint. Afterwards, this can easily be removed with a spatula or scraper. The temperature of the treated surface should be between 7°C and 30°C. Tip: to prevent the solvent from evaporating from the paint stripper, a plastic sheet can be placed over the layer.

Safety:

Harmful if inhaled, swallowed and in contact with skin. Irritating to skin and eyes.
Always wear protective clothing, safety glasses and gloves. Keep out of reach of children.
Dispose of empty packaging in accordance with the applicable local and national regulations.
Cleaning agent for tools: cleaner M